



IPC 2U-2404S

The **IPC 2U-2404S** is the perfect rack for a low-priced storage system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-2404S** offers the possibility to mount maximal four 2.5" or 3.5" Hot-Swap HDDs and one internal 2.5" or 3.5" HDD (by using a 2.5" with 9.5mm height also a 3.5" HDD simultaneously). The **IPC 2U-2404S** is equipped with three serial 40mm fans. At the rear of the chassis you can mount an ATX PSU with 80mm fan.

Specifications

Motherboard	Mini-ITX, µATX
max. motherboard size WxD: 244mm x 244mm, 9.6" x 9.6"	
Drive Bays	2.5" or 3.5" Hot-Swap (max. 12G): 4 2.5" or 3.5" internal: 1 ¹
Front Connectors	USB 3.0: 2
Cooling System	Internal: 3x 40mm (serial, 3Pin with 4Pin connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity 1x Alert
Power Supply	ATX PSU with 80mm fan
Material	1.0-1.2mm steel
Maximum CPU cooler height	32mm/65mm*
Maximum graphics card length	190mm
Packing Units	Shipping Unit: 1 Piece Pallet: 21 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887190
EAN-Code	4260133128613
Scope of Delivery	Screw Set Mounting frame for ATX PSU Mounting tool
Features	Serial 3x 40mm fans 4x perforated Low-Profile slot bracket (Rear) USB 3.0 internal as block connector Hot-Swap backplane with SFF 8643 socket (max. 12 G) ² Mesh-Grid-Front

¹simultaneously only if 2.5" drive with max. 9.5 mm height

² The backplane is only compatible with a SAS-Controller with SFF-8643connector.

To use the backplane with a SATA-Controller, please order the optional SFF8643 cross-over cables (88885670) in right quantity
*depending on the position of the CPU (32mm, if the CPU is under the HDD cage)

Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	155mm
Width	433mm	482mm	550mm
Depth	400mm	438mm	560mm
Weight (net): 5.97kg			
Weight (gross): 7.67kg			

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

