



Model: 2U-2724

Art.: 88887383

2U high-performance storage enclosure with 24x 2.5" hot-swap bays (SAS3 / SATA / NVMe)

Maximum storage density in the smallest of spaces – the 2U storage enclosure has been specially developed for demanding server and storage applications. With **24 hot-swap bays for 2.5" drives** and support for **SAS3, SATA, and NVMe**, it combines outstanding flexibility with maximum performance.

Highlights at a glance:

- **24x 2.5" hot-swap removable frames** – compatible with SAS3, SATA, and NVMe SSDs/HDDs
- **Wide motherboard support:** Mini-ITX, Micro-ATX, ATX, and E-ATX
- **Optimized cooling:** 3x powerful 80mm hot-plug fans for maximum operational reliability
- **Practical extras:** UUID switch, UUID alarm LED, and ID card holder for professional rack organization
- **Additional storage space:** 2 internal 2.5" slots for operating system or cache drives

Flexible. Robust. Future-proof.

The sturdy steel housing is designed for continuous operation in data centers and offers sufficient space for a wide variety of motherboard formats. Thanks to **UUID management** and **alarm LEDs**, administrators always have an overview of system status and identification.

Features		24x removable frames 2.5" Hot-swap backplane with SATA/SAS3/ NVMe sockets 3x 80mm fans as standard UUID support ID card holder
Backplane	Quantity Backplanes	3
	Quantity hard disks	8/ Backplane
	Transfer speed	SATA 6 Gb/s SAS 12 Gb/s NVMe 16 Gb/s
	Data connection	2x SATA/SAS (SFF8654-4i) + 4x NVMe (SFF8654-8i) per backplane
	Electrical connection	1x 4-Pin/ Backplane
Size	Mainboard	Mini-ITX, mATX, ATX, E-ATX (max. 305 x 330mm - 12" x 13")
	Case	481 x 700 x 87mm (WxDxH)
	Cage	447 x 670 x 87mm (WxDxH)
HDD/ ODD Mounting space	5.25" external	-
	3.5" external	-
	3.5" or 2.5" external	24 (Hot-Swap)
	3.5" internal	-
	2.5" internal	2
	3.5" od. 2.5" intern	-
Front connectors	USB A 3.0	2x 3.2 Gen1
	USB A 2.0	-
	USB Type C	-
	Headphone	-
	Microphone	-
	Card Reader	-
Mounted fans	200mm	-

140mm	-
120mm	-
80mm	3
	2 ball bearing Voltage: 12V Speed: 6000 U/m Air flow: 136 cbm/h Static pressure: 21.6 mm-H2O Noise level: 57dbA Dimensions: 80x80x38mm
60mm	-

Further mounting options	Power supply	ASPOWER 2U and 2U Redundant (DV series)
	CPU cooler	max. 70mm
	Graphic adapter	max. 330mm (Low-Profile)
	Fans	-

Scope of delivery	Case Mounting frame for 2U power supply Screws Adapter cable for backplane power connection (12V 4-pin to Molex)
--------------------------	---

Warranty	24 Months
-----------------	-----------

Logistic data	Net weight	10.19 kgs
	Gross weight	14.36 kgs
	Article number	88887383
	GTIN	4260455648172
	Packing unit	1 pcs 12 pcs (pallet)

